



http://192.168.254.123/



http://192.168.254.123/

Google

Composez le **#*111#** sur le téléphone connecté à l'ATA, puis recopiez l'adresse IP qui vous sera communiquée (par ex: 192.168.2.7) tel quel dans la barre d'adresse de votre browser (Explorer, Firefox, etc ...)

Username: Password:

Le username / password par défaut est admin / admin

Current State

Network

WAN Config

LAN Config

VoIP

SIP Config

IAX2 Config

Advance

DHCP Server

NAT

Net Service

QOS

SIP

Digital Map

Call Service

MMI Filter

Audio Settings

VPN

Dial-Peer

Config Manage

Save Config

Clear Config

Backup Config

Update

WEB Update

FTP/TFTP Update

Auto Provisioning

System Manage

Account Management

Syslog Config

Time Config

Logout & Reboot

SIP[Registered] Configuration

Register Server Addr	<input type="text" value="85.119.188.3"/>	Proxy Server Addr	<input type="text"/>
Register Server Port	<input type="text" value="5060"/>	Proxy Server Port	<input type="text"/>
Register Username	<input type="text" value="03555 xxxx"/>	Proxy Username	<input type="text"/>
Register Password	<input type="password" value="*****"/>	Proxy Password	<input type="password"/>
Domain Realm	<input type="text" value="85.119.188.3"/>	Local SIP Port	<input type="text" value="5060"/>
Phone Number	<input type="text" value="03555 xxxx"/>	Register Expire Time	<input type="text" value="60"/> seconds
Detect Interval Time	<input type="text" value="60"/> seconds	RFC Protocol Edition	<input type="text" value="RFC2543"/>
Encrypt Key	<input type="text"/>	Server Type	<input type="text" value="common"/>
Display Name	<input type="text"/>	User Agent	<input type="text" value="Volp Phone 1.0"/>
DTMF Mode	<input type="text" value="DTMF_SIP_INFO"/>	<input type="checkbox"/> Signal Encrypt	
<input type="checkbox"/> Enable PRACK		<input type="checkbox"/> Rtp Encrypt	
<input checked="" type="checkbox"/> Enable Keep Authentication		<input type="checkbox"/> Enable Session Timer	
<input checked="" type="checkbox"/> Auto Detect Server		<input type="checkbox"/> Answer With Single Codec	
<input checked="" type="checkbox"/> Enable Via rport		<input checked="" type="checkbox"/> SIP(Default Protocol)	
<input checked="" type="checkbox"/> Enable Register			

Apply

Current State

Network

WAN Config
LAN Config

VoIP

SIP Config
IAX2 Config ◀

Advance

DHCP Server
NAT
Net Service
QOS
SIP
Digital Map
Call Service
MMI Filter
Audio Settings
VPN

Dial-Peer

Config Manage

Save Config
Clear Config
Backup Config

Update

WEB Update
FTP/TFTP Update
Auto Provisioning

System Manage

Account Management
Syslog Config
Time Config
Logout & Reboot

IAX[Unregistered] Configuration

IAX Server Addr	<input type="text"/>
IAX Server Port	<input type="text" value="4569"/>
Account Name	<input type="text"/>
Account Password	<input type="text"/>
Phone Number	<input type="text"/>
Local Port	<input type="text" value="4569"/>
Voice mail number	<input type="text" value="0"/>
Voice mail text	<input type="text" value="mail"/>
Echo Test number	<input type="text" value="1"/>
Echo Test text	<input type="text" value="echo"/>
Refresh Time	<input type="text" value="60"/> Seconds
<input type="checkbox"/> Enable Register	<input checked="" type="checkbox"/> Enable G.729
<input type="checkbox"/> IAX(Default Protocol)	

Apply

VoIP Gateway

Current State

Network

WAN Config
LAN Config

VoIP

SIP Config
IAX2 Config

Advance

DHCP Server
NAT
Net Service
QOS

SIP

Digital Map
Call Service
MMI Filter
Audio Settings
VPN

Dial-Peer

Config Manage

Save Config
Clear Config
Backup Config

Update

WEB Update
FTP/TFTP Update
Auto Provisioning

System Manage

Account Management
Syslog Config
Time Config
Logout & Reboot

Advance SIP Configuration

Public[Registered]Private[Unregistered]
STUN NAT Transverse[FALSE]

STUN Server Addr	<input type="text"/>	STUN Server Port	<input type="text" value="3478"/>
Private Server Addr	<input type="text"/>	Private Proxy	<input type="text"/>
Server Port	<input type="text" value="5060"/>	Proxy Port	<input type="text"/>
Server Username	<input type="text"/>	Proxy Username	<input type="text"/>
Server Password	<input type="text"/>	Proxy Password	<input type="text"/>
Private Domain	<input type="text"/>	Expire Time	<input type="text" value="60"/> seconds
Private Number	<input type="text"/>	STUN Effect Time	<input type="text" value="50"/> minute
Display Name	<input type="text"/>	Private User Agent	<input type="text" value="Voip Phone 1.0"/>
Private Server Type	<input type="text" value="common"/>	<input checked="" type="checkbox"/> Enable URI Convert	
<input type="checkbox"/> Enable Private Register		<input type="checkbox"/> Enable SIP Stun	

Apply

Current State

Network

[WAN Config](#)
[LAN Config](#)

VoIP

[SIP Config](#)
[IAX2 Config](#)

Advance

[DHCP Server](#)
[NAT](#)
[Net Service](#)
[QOS](#)
[SIP](#)
[Digital Map](#)
[Call Service](#)
[MMI Filter](#)
[Audio Settings](#)
[VPN](#)

Dial-Peer

Config Manage

[Save Config](#)
[Clear Config](#)
[Backup Config](#)

Update

[WEB Update](#)
[FTP/TFTP Update](#)
[Auto Provisioning](#)

System Manage

[Account Management](#)
[Syslog Config](#)
[Time Config](#)
[Logout & Reboot](#)

DSP Configuration

CODEC	<input type="text" value="g711Alaw64k"/>	Signal Standard	<input type="text" value="UK"/>
Input Volume	<input type="text" value="2"/> (0-5)	Output Volume	<input type="text" value="2"/> (0-5)
G729 Payload Length	<input type="text" value="10"/> ms	DTMF Payload Type	<input type="text" value="101"/>
iLBC Payload Type	<input type="text" value="97"/> (96-127)	iLBC Payload Length	<input type="text" value="30"/> ms
CallerID Tx Mode	<input type="text" value="DTMF"/>	FAX Mode	<input type="text" value="T.38"/>
<input checked="" type="checkbox"/> VAD			

VoIP Gateway

Current State

Network

WAN Config
LAN Config

VoIP

SIP Config
IAX2 Config

Advance

DHCP Server
NAT
Net Service
QOS
SIP
Digital Map
Call Service
MMI Filter
Audio Settings
VPN

Dial-Peer

Config Manage

Save Config ◀
Clear Config
Backup Config

Update

WEB Update
FTP/TFTP Update
Auto Provisioning

System Manage

Account Management
Syslog Config
Time Config
Logout & Reboot

Save Configuration

Save

VoIP Gateway

Current State

Network

WAN Config
LAN Config

VoIP

SIP Config
IAX2 Config

Advance

DHCP Server
NAT
Net Service
QOS
SIP
Digital Map
Call Service
MMI Filter
Audio Settings
VPN

Dial-Peer

Config Manage

Save Config
Clear Config
Backup Config

Update

WEB Update
FTP/TFTP Update
Auto Provisioning

System Manage

Account Management
Syslog Config
Time Config
Logout & Reboot

Reboot System

Reboot

Logout